

## Manufacturer/Supplier:

WUXI DONGLIN SCI&TECH DEVELOPMENT CO., LTD

Address: A1-203 Mingpin CityII, No.8 Xihudong Road. Liangxi District

Wuxi Jiangsu Province, China

TELE: 86-510-82732223 FAX: 86-510-82720101-8014

**Web**: www.dldevelop.com

Email: info@dldevelop.com.cn service@dldevelop.com.cn

Product name: Rabbit anti-CALCOCO1 Antibody

**Catalog:** DL96573A

**Synonyms:** KIAA1536; Calcium-binding and coiled-coil

domain-containing protein 1; Calphoglin;

Coiled-coil coactivator protein; Sarcoma antigen

NY-SAR-3

Immunogen: Recombinant full length protein of human

CALCOCO1

Form: Liquid Concentration: 1mg/mL

Size: 100 u1/50 u1 Host: Rabbit

**Reactivity:** Human **Application:** WB, IHC, IF/IC



**Clonality:** Polyclonal **Dilution:** WB (1/500 - 1/2000),

IHC (1/50 - 1/200), IF/IC (1/50 -

1/100)

Entrez Gene: 57658

O9P1Z2 SwissProt:

**Purification:** The antibody was purified by immunogen affinity

chromatography.

**Buffer:** Liquid in 0.42% Potassium phosphate, 0.87%


Sodium chloride, pH 7.3, 30% glycerol, and 0.01%

sodium azide.

## **WB** description:

Western blot analysis of CALCOCO1 expression in MCF7 (A), A549 (B), mouse lung (C), mouse heart (D) whole cell lysates.






## **IHC** description:

Immunohistochemical analysis of CALCOCO1 staining in human kidney formalin fixed paraffin embedded tissue section. The section was pre-treated using heat mediated antigen retrieval with sodium citrate buffer (pH 6.0). The section was then incubated with the antibody at room temperature and detected using an HRP conjugated compact polymer system. DAB was used as the chromogen. The section was then counterstained with haematoxylin and mounted with DPX.

## **IF/ICC description:**

Immunofluorescent analysis of CALCOCO1 staining in A549 cells. Formalin-fixed cells were permeabilized with 0.1% Triton X-100 in TBS for 5-10 minutes and blocked with 3% BSA-PBS for 30 minutes at room temperature. Cells were probed with the primary antibo





**Storage:** Store at -20°C. Avoid repeated freeze / thaw cycles.